

# VC Tiles

## PRODUCT SPECIFICATION

### KEY FEATURES

- Classic economical value.
- Consists of vinyl composition tiles.
- Provides durable flooring.
- Perfect for supermarkets, retail stores, schools and storage areas.



PRODUCT FORMAT	Standard	Result
Gauge	ISO 24346 (EN 428)	3.0mm (2.0mm only in Western Australia)
Total Weight	ISO 23997 (EN 430)	4400g/m <sup>2</sup>

TILE SIZE	Size	Shades	Quantity per Box	Coverage per Box/Roll
Tile	300mm x 300mm	9	55	4.95m <sup>2</sup>

PERFORMANCE REQUIREMENTS	Standard	Result
General Performance	ISO 10595 : 2012 (BS EN)	Conforms
Slip Resistance	AS 4586 App D	Product is intended to be sealed once installed, slip performance should be considered with regards to the sealer used
Reaction to Fire	AS ISO 9239.1	≥ 8kW/m <sup>2</sup>
Residual Indentation	ISO 24343-3 (EN 433)	<0.10
Dimensional Stability	ISO 23999 (EN 434)	≤0.20%
Flexibility	ISO 24344 (Method B)	≤25mm

Application

Polyflor VC Tile range is recommended as a cost effective flooring solution for public and commercial buildings, e.g. supermarkets, retail, stores, schools, commercial premises, storage areas. For further advice on specific applications consult Polyflor.

# VC Tiles

RANGE SHADES

9 Shades



**157 MOONDUST**  
300 x 300mm




**173 CAPPUCCINO**  
300 x 300mm




**727 EIFFEL TOWER**  
300 x 300mm



**1102 PEBBLE**  
300 x 300mm



**1104 DUSKY GREY**  
300 x 300mm



**1107 STORM CLOUD**  
300 x 300mm



**1117 MERINO**  
300 x 300mm



**2222 MOSSMAN**  
300 x 300mm



**2230 NOUGAT**  
300 x 300mm

With regard to colour printing, it is only possible to give a provisional representation of the product colour. For colour selection an original sample should be used, which we shall be pleased to supply free of charge. To replicate the natural material, the stone effect tiles may include variation in markings as part of their design.