

Expona Flow PUR



PRODUCT SPECIFICATION

Key Features

- > Contemporary wood, stone & abstract designs
- > Durable vinyl sheet format
- > Low VOC emissions
- > Low cost, polish-free maintenance
- > Heavy commercial installations



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.70mm
Total Weight	ISO 23997 (EN 430)	2660g/m ²
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	50	-	40m ²

Performance Requirements	Standard	Result
General Performance	ISO 10582 (EN 649) ASTM F1303	Conforms Type I, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E648 AS ISO 9239.1	Class Bfl-S1 Class 1 ≥ 8kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F1914 ASTM F970 (Modified) ISO 24343-1	<0.005" <0.005" (750psi) ≤0.10mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
Flexibility	ISO 24344 (EN 435) ASTM F137	(Method A) Pass 20mm ø 0.25" Pass
Underfloor Heating		Suitable, max 27°C

Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 415
GreenTag		GreenRate Level A, LCA Rate Silver Plus
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance

	Standard	Result
Impact Sound Reduction	ISO 10140-3	8dB

Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene

	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth



BS EN 14041

EN 14041

Polyflor Head Office

101 Prosperity Way, Dandenong South, VIC, 3175 • Tel: 1800 777 425 • Email: sales@polyflor.com.au • www.polyflor.com.au

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.


Expona Flow PUR



RANGE SHADES



White Pine 9834
plank size in sheet: 166 x 1500mm
w/r 9834 LRV 57




Painted Chevron 9828
plank size in sheet: 120 x 700mm
w/r 9828 LRV 43



Sun Bleached Oak 9825
plank size in sheet: 200 x 1500mm
w/r 9825 LRV 31




Silver Oak 9826
plank size in sheet: 200 x 1500mm
w/r 9826 LRV 28



Grey Weathered Chevron 9829
plank size in sheet: 120 x 700mm
w/r 9829 LRV 26



Classic Limed Ash 9833
plank size in sheet: 166 x 1500mm
w/r 9833 LRV 49




Warm Limed Ash 9832
plank size in sheet: 166 x 1500mm
w/r 9832 LRV 34




Blond Pine 9839
plank size in sheet: 166 x 1500mm
w/r 9839 LRV 37



Blond Oak 9820
plank size in sheet: 167 x 1500mm
w/r 9820 LRV 28




Roasted Limed Ash 9831
plank size in sheet: 166 x 1500mm
w/r 9831 LRV 27



English Oak 9823
plank size in sheet: 200 x 1500mm
w/r 9823 LRV 24




Golden Pine 9838
plank size in sheet: 166 x 1500mm
w/r 9838 LRV 25




Reclaimed Chevron 9830
plank size in sheet: 120 x 700mm
w/r 9830 LRV 17




Honey Oak 9821
plank size in sheet: 167 x 1500mm
w/r 9821 LRV 22



Toasted Oak 9822
plank size in sheet: 167 x 1500mm
w/r 9822 LRV 18




Bronzed Pine 9835
plank size in sheet: 166 x 1500mm
w/r 9835 LRV 14




Aged Oak 9824
plank size in sheet: 200 x 1500mm
w/r 9824 LRV 8



Silvered Pine 9836
plank size in sheet: 166 x 1500mm
w/r 9836 LRV 17



Smoked Oak 9827
plank size in sheet: 200 x 1500mm
w/r 9827 LRV 11




Charcoal Pine 9837
plank size in sheet: 166 x 1500mm
w/r 9837 LRV 13




Honey Beige 9869
NCS S 3005-Y50R
w/r 9869 LRV 29




Auburn 9863
NCS S 5020-Y30R
w/r 9863 LRV 17



Espresso 9867
NCS S 7005-Y80R
w/r 9867 LRV 10



Autumn Rain 9864
NCS S 5005-Y80R
w/r 9864 LRV 24



Firelight 9868
NCS S 5020-Y40R
w/r 9868 LRV 16


Expona Flow PUR




Night Sky **9865**
NCS S 7000-N
w/r 9865 LRV 13




Raven **9866**
NCS S 7502-R
w/r 9866 LRV 12




Luna **9844**
NCS S 1502-B
w/r 9844 LRV 48




Storm **9845**
NCS S 3502-B
w/r 9845 LRV 26




Jet **9842**
NCS S 8000-N
w/r 9842 LRV 8



Steel Blue **9852**
NCS S 6020-B10G
w/r 9852 LRV 10




Midnight **9854**
NCS S 7005-R80B
w/r 9854 LRV 10




Oatmeal **9840**
NCS S 2005-G90Y
w/r 9840 LRV 43




Moleskin **9841**
NCS S 3005-Y20R
w/r 9841 LRV 28



Taupe **9843**
NCS S 7502-Y
w/r 9843 LRV 10



Teal **9851**
NCS S 6020-B70G
w/r 9851 LRV 11



Woodland **9853**
NCS S 6020-B50G
w/r 9853 LRV 11




Flaxen **9849**
NCS S 0560-Y
w/r 9849 LRV 44




Meadow **9850**
NCS S 2050-G90Y
w/r 9850 LRV 32



Burnt Orange **9848**
NCS S 3040-Y40R
w/r 9848 LRV 24



Mulberry **9846**
NCS S 6010-R30B
w/r 9846 LRV 13




Plum **9847**
NCS S 6020-R10B
w/r 9847 LRV 9



Light Grey Concrete **9858**
NCS S 3000-N
w/r 9858 LRV 40



Cool Concrete **9856**
NCS S 4500-N
w/r 9856 LRV 22



Warm Concrete **9855**
NCS S 3502-R
w/r 9855 LRV 25



Dark Grey Concrete **9857**
NCS S 6502-R
w/r 9857 LRV 13



Light Industrial Concrete **9860**
NCS S 2500-N
w/r 9860 LRV 35



Dark Industrial Concrete **9859**
NCS S 4502-R
w/r 9859 LRV 24



Copper Ornamental **9861**
NCS S 5502-R
w/r 9861 LRV 19



Onyx Ornamental **9862**
NCS S 7000-N
w/r 9862 LRV 11

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Head Office

101 Prosperity Way, Dandenong South, VIC, 3175 • Tel: 1800 777 425 • Email: sales@polyflor.com.au • www.polyflor.com.au

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.