

Polysafe Verona PUR: *Original*



PRODUCT SPECIFICATION

Key Features

- > Sustainable, slip resistant safety vinyl flooring
- > Virtually invisible slip resistant particles
- > Pendulum test - 36+ (slider 96)
- > Polysafe PUR for superior cleaning benefits
- > Suited to heavy traffic areas with risk of spillage



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	2600g/m ²
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	18	-	40m ²

Performance Requirements	Standard	Result
General Performance	EN 13845 ASTM F1303	Conforms Type II, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845 RRL Pendulum Test AS 4586 Appendix A AS 4586 Appendix D DIN 51130 / DIN EN 16165 Ann. B Surface Roughness ASTM D2047	ESf ≥36 (wet test - 4S Rubber / Slider 96) P3 (Slider 96) R10 R10 Rz ≥20µm SCOF ≥0.8
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2 AS ISO 9239-1	Class Bfl-S1 Class 1 FSV < 300; SDV < 500 >8.0kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750psi)
Flexibility	ASTM F137	1.5" Pass
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 472
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		Contains recycled material
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene

	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth



BS EN 14041

EN 14041

Polyflor Head Office

101 Prosperity Way, Dandenong South, VIC, 3175 • Tel: 1800 777 425 • Email: sales@polyflor.com.au • www.polyflor.com.au

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1


Polysafe Verona PUR: *Original*




RANGE SHADES



Cookie Cream 5201 w/r 5201
NCS S 1502-Y LRV 64




Biscotti 5212 w/r 5212
NCS S 3005-Y20R LRV 45




Marshmallow 5214 w/r 5214
NCS S 3005-Y50R LRV 45




Caramel Latte 5213 w/r 5213
NCS S 3010-Y40R LRV 34



Rainstorm 5202 w/r 5202
NCS S 2502-G LRV 44




Dolphin Grey 5203 w/r 5203
NCS S 4500-N LRV 26




Blue Lagoon 5206 w/r 5206
NCS S 2030-R90B LRV 32




Freshmint 5209 w/r 5209
NCS S 2010-B30G LRV 52




Skyline 5205 w/r 5205
NCS S 2010-B LRV 47




Horizon Blue 5208 w/r 5208
NCS S 3020-R90B LRV 31




Nightfall 5207 w/r 5207
NCS S 6010-R90B LRV 12




Summer Coulis 5217 w/r 5217
NCS S 4020-Y90R LRV 21



Oregano 5210 w/r 5210
NCS S 2005-G70Y LRV 48




Seagrass 5211 w/r 5211
NCS S 4010-B50G LRV 25




Soft Peach 5216 w/r 5216
NCS S 1515-Y60R LRV 47



Butterscotch 5218 w/r 5218
NCS S 2030-Y30R LRV 35



Chocolate Chip 5215 w/r 5215
NCS S 6005-Y50R LRV 16



Cafe Noir 5204 w/r 5204
NCS S 7000-N LRV 11

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polysafe Head Office

101 Prosperity Way, Dandenong South, VIC, 3175 • Tel: 1800 777 425 • Email: sales@polyflor.com.au • www.polyflor.com.au

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1