

TECHNICAL DETAILS

The following table details the technical specification for the Native Collection.
Should you require any further information, contact Polyflor on 1800 777 425 or email technical@polyflor.com.au

Characteristics	Standards	Native Collection
General performance	EN 649 / EN ISO 10582	Heterogeneous, PVC
Surface treatment		PUR
Total weight	EN 430 / EN ISO 23997	4290 g/m ²
Performance classification	EN 685 / EN ISO 10874	23 / 33 / 42
Gauge	EN 428 / EN ISO 24346	2.5mm
Wear layer thickness	EN 429 / EN ISO 24340	0.55mm
Packaging plank size	EN 427 / EN ISO 24342	12 @ 184.2 x 1524mm = 3.37m ²
Abrasion group	EN 660-2	T
Binder content	EN ISO 10582	Type I
Residual indentation	EN 433 / EN ISO 24343-1	Pass
Colour fastness to artificial light	EN ISO 105-B02	≥6
Behaviour to fire	AS ISO 9239.1	Meets requirements of the NCC
Slip resistance	AS 4586 App D	R10
Electrical behaviour	EN 1815	≤2kV Antistatic
Chemical resistance	EN 423 / EN ISO 26987	*
Castor chair suitability	EN 425 / ISO 4918	Yes
Underfloor heating suitability	EN 1264-2	Suitable, max 27°C
Sound reduction	ISO 10140-3	2 dB
AgBB VOC test		Very low emissions



* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals - please contact us.

Subject to changes for reasons of technical further development.